

Access 8 AHpin

Keypad reader



The Access 8 AHpin readers support the globally spread PROX-technology by HID®. They are designed for reliable and secure access control, data collection and people identification. Access 8 AHpin is available with Wiegand and Clock&Data interfaces.

The Access 8 AHpin improves security in access control by providing pin code identification to be used together with an identification card. The keypad of the reader is based on EMFi foil technology. The EMFi foil senses pressure changes on the active key area when pressed. The foil as well as the electrical parts of the reader are cast in epoxy and are therefore safe from damage inside the reader.

The Access 8 AHpin is available in black. Customised colour options and logos are available on request. Access 8 AHpin reader is also available as Access Exclusive model option with hand-made wooden and stone housings.

Specifications

Voltage	24 VDC (10 VDC ... 30 VDC)
Current consumption	max 130 mA
Interfaces:	Wiegand (26- or 37-bit), Clock&Data
Material of design housing	Plastic
Dimensions of housing (hwxwd)	138 x 44 x 24 mm
Operating temperature	-40...+55 °C
Storage temperature	-40...+55 °C
Protection class	IP47
Cable	LIYY 3 m
Led	Tricolour
Led control	Cable / configurable
Buzzer	Yes
Buzzer control	Cable / configurable
Carrier frequency	125 kHz
Field strength	According to the EN300330
Certifications	CE Europe FCC United States IC Canada

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes.
All trademarks and registered trademarks are property of their respective owners.
C00311E v1.00 15.3.2010.