

## Access 8 CM t Configuration

Conf_number	W/CD	Datalength	Parity	Invert ID	Pin-code	Send UID	Backlight	Timings				Mifare Key
								1	2	3	4	
Conf_1	Wiegand	26-bit	on	off	8 beep on	on	off	70	930	70	930	414343455353
Conf_2	Wiegand	64-bit	off	off	8 beep on	on	on	100	2000	100	2000	Customer
Conf_3	Wiegand	32-bit	off	off	4 beep on	on	off	70	930	70	930	Customer
Conf_4	Wiegand	88-bit	off	off	8 beep on	on	off	70	930	70	930	Customer
Conf_5	Wiegand	36-bit	on	off	4 beep on	off	off	100	1000	100	1000	FFFFFFFFFFFF
Conf_6	Wiegand	66-bit	on	off	8 beep on	on	off	70	930	70	930	Customer
Conf_7	CD	BCD 10	off	off	4 beep on	off	off	100	1000	100	1000	FFFFFFFFFFFF
Conf_8	Wiegand	26-bit	on	off	8 beep on	off	on	70	930	70	930	414343455353
Conf_9	Wiegand	62-bit	on	off	8 beep on	on	on	100	1000	100	1000	Customer
Conf_10	Wiegand	34-bit	on	off	8 beep on	on	off	70	930	70	930	Customer
Conf_11	Wiegand	34-bit	on	off	8 beep on	on	off	70	930	70	930	Customer
Conf_12	Wiegand	34-bit	off	off	8 beep on	off	off	70	930	70	930	Customer
Conf_13	Wiegand	34-bit	off	off	8 beep on	off	off	70	930	70	930	Customer
Conf_14	Wiegand	26-bit	off	off	8 beep on	off	off	100	2000	100	2000	Customer